

# DATA SHEET SEESAW ACULA

Text for invitation to tender | Item No: 51 2517 601

## MATERIALS | SCOPE OF SUPPLY

Seesaw, pre-mounted completely

Seesaw bar:	stainless steel, V2A
Rack:	stainless steel, V2A with shaft made of stainless steel and sockets made of plastic
Seats:	structural composite lumber, larch, 2 pieces
Handles:	stainless steel, V2A, with EPDM caoutchouc ball, 4 pieces
Foundation plates:	steel, coated

## TECHNICAL INFORMATION

Dimensions:

Main dimension:	3200 x 460 mm
Height:	840 mm
Weight:	100 kg
Capacity:	acc. to normative requirements
Dimension largest piece:	3200 x 480 x 1290 mm
Heaviest piece:	100 kg

Max. fall height:	900 mm
Impact area:	13,00 m <sup>2</sup>
Required safety slabs:	13,75 m <sup>2</sup>
Required lawn grating:	18,00 m <sup>2</sup>
Recommended surface material:	grass, sand, wood chip, gravel, synth. impact protection

## INSTALLATION

Foundations: 1 foundation, plus 2 foundations for seesaw softeners

Modified installation depth possible (special edition)

Seesaw softeners must be concreted.

Installation according to our detailed mounting instructions, see [www.stilum.com](http://www.stilum.com)

Please note the material information in the mounting- and maintenance instruction.

