

DATA SHEET SEESAW ACULA

Text for invitation to tender | Item No: 51 2517 601



MATERIALS | SCOPE OF SUPPLY

Seesaw, pre-mounted completely

Seesaw bar:	stainless steel, V2A
Rack:	stainless steel, V2A with shaft made of stainless steel and sockets made of plastic
Seats:	structural composite lumber, larch, 2 pieces
Handles:	stainless steel, V2A, with EPDM caoutchouc ball, 4 pieces
Foundation plates:	steel, coated

TECHNICAL INFORMATION

Dimensions:

Main dimension:	3200 x 460 mm
Height:	840 mm
Weight:	100 kg
Capacity:	acc. to normative requirements
Dimension largest piece:	3200 x 480 x 1290 mm
Heaviest piece:	100 kg

Max. fall height:	900 mm
Impact area:	13,00 m ²
Required safety slabs:	13,75 m ²
Required lawn grating:	18,00 m ²
Recommended surface material:	grass, sand, wood chip, gravel, synth. impact protection

INSTALLATION

Foundations: 1 foundation, plus 2 foundations for seesaw softeners

Modified installation depth possible (special edition)

Seesaw softeners must be concreted.

Installation according to our detailed mounting instructions, see www.stilum.com

Please note the material information in the mounting- and maintenance instruction.

