

DATA SHEET CABLEWAY AGILA ROBINIA

Text for invitation to tender | Item No: 51 7021 601



MATERIALS | SCOPE OF SUPPLY

Cableway, in lengths 20m/ 25m/ 30m or 35m,
final assembly on location

Rack:	post made of stainless steel, V2A, 2 pieces, post made of robinia with pedestal made of stainless steel, 4 pieces
Pendulum seat:	EPDM caoutchouc, 1 piece
Cableway trolley:	1 piece
Brake spring:	length 1,50 m, 1 piece length 3,00 m, 1 piece
Cable tensioner:	stainless steel, 1 piece
Cable:	galvanized steel, 1 piece
Climb:	Stainless steel, V2A, with 2 plateaus made of steel with surface made of EPDM granules, 1 piece
Foundation plates:	steel, coated

INSTALLATION

Foundations: 4

Installation according to our detailed mounting instructions, see www.stilum.com

Please note the material information in the mounting- and maintenance instruction.

TECHNICAL INFORMATION

Dimensions:

Main dimension rack 1:	3050 x 2000 mm
Height rack 1:	3700 mm
Main dimension rack 1:	2190 x 1520 mm
Height rack 1:	2700 mm
Length L:	20m/ 25m/ 30m/ 35m
Weight:	680 kg - 690 kg
Capacity:	acc. to normative requirements
Dimension largest piece:	300 x 470 x 5500 mm
Heaviest piece:	78 kg

Max. fall height:	1700 mm
Impact area:	105m ² / 125m ² / 145m ² / 165m ²
Required safety slabs:	106m ² / 126m ² / 146m ² / 166m ²
Required lawn grating:	108m ² / 128m ² / 148m ² / 168m ²
Recommended surface material:	sand, wood chip, gravel, synth. impact protection

