

DATA SHEET SPRINGRIDER ALTUS 1 SADDLE

Text for invitation to tender | Item No: 51 3020 402



MATERIALS | SCOPE OF SUPPLY

Springrider, pre-mounted completely

Tubular frame:	stainless steel, V2A
Spring:	torsion spring made of steel with rubber core, 1 piece
Saddle seat:	EPDM caoutchouc with steel inlay, 1 piece
Handles:	stainless steel, V2A, with caps made of plastic, 2 pieces
Foot rest:	stainless steel, V2A, with caps made of plastic, 2 pieces
Foundation anchor:	galvanized steel

TECHNICAL INFORMATION

Dimensions:

Main dimension:	730 x 470 mm
Height:	680 mm
Weight:	22 kg
Capacity:	acc. to normative requirements
Dimension largest piece:	730 x 500 x 1180 mm
Heaviest piece:	22 kg

Max. fall height:	500 mm
Impact area:	6,64 m ²
Required safety slabs:	7,50 m ²
Required lawn grating:	9,00 m ²
Recommended surface material:	grass, sand, wood chip, gravel, synth. impact protection

INSTALLATION

Foundations: 1
Modified installation depth possible (special edition)

Installation according to our detailed mounting instructions, see www.stilum.com

