

DATA SHEET SPRINGRIDER ALTUS 2 SADDLE

Text for invitation to tender | Item No: 51 3021 402



MATERIALS | SCOPE OF SUPPLY

Springrider, pre-mounted completely

| | |
|--------------------|---|
| Tubular frame: | stainless steel, V2A |
| Spring: | torsion spring made of steel with rubber core, 1 piece |
| Saddle seat: | EPDM caoutchouc with steel inlay, 2 pieces |
| Handles: | stainless steel, V2A, 2 pieces with caps made of plastic, 4 pieces |
| Foot rest: | stainless steel, V2A, 2 pieces, with caps made of plastic, 4 pieces |
| Foundation anchor: | galvanized steel |

TECHNICAL INFORMATION

Dimensions:

| | |
|--------------------------|--------------------------------|
| Main dimension: | 1490 x 470 mm |
| Height: | 850 mm |
| Weight: | 36 kg |
| Capacity: | acc. to normative requirements |
| Dimension largest piece: | 1490 x 500 x 1350 mm |
| Heaviest piece: | 36 kg |

| | |
|-------------------------------|--|
| Max. fall height: | 700 mm |
| impact area: | 8,64 m ² |
| Required safety slabs: | 10,00 m ² |
| Required lawn grating: | 12,00 m ² |
| Recommended surface material: | grass, sand, wood chip, gravel, synth. impact protection |

INSTALLATION

Foundations: 1
Modified installation depth possible (special edition)

Installation according to our detailed mounting instructions, see www.stilum.com

