

DATA SHEET MULTIPLAY GRAVIS 2A

Text for invitation to tender | Item No: 51 5519 421



MATERIALS | SCOPE OF SUPPLY

Climbing equipment, final installation on location

Tower:	stainless steel, V2A, with steel plateau which surface is made of EPDM granules, and roof made of HDPE panel, 2 pc.
Post:	stainless steel, V2A, 6 pieces
Climbing net:	Herkules rope/plastic, 1 piece
Climbing balls:	stainless steel, V2A, with 4 balls made of EPDM granules, 1 piece
Layaway bow:	stainless steel, V2A with 12 caps made of plastic, 1 pc.
Climbing wall:	stainless steel, V2A, with 2 HDPE panels, 1 piece
Wobble bridge:	Herkules rope/plastic/wood, 1 pc.
Parallel bars slide:	stainless steel, V2A, 1 piece
Slide:	stainless steel, V2A, 1 piece
Caps:	plastic, 2 pieces
Decoration ball:	EPDM granules, 4 pieces
Foundation plates:	steel, coated

INSTALLATION

Foundations: 10

Installation according to our detailed mounting instructions, see www.stilum.com

TECHNICAL INFORMATION

Dimensions:

Main dimension:	4250 x 9500 mm
Height:	3320 mm
Weight:	880 kg
Capacity:	acc. to normative requirements
Dimension largest piece:	2550 x 700 x 3500
Heaviest piece:	185 kg

Max. fall height:	2200 mm
Impact area:	71,34 m ²
Required safety slabs:	min. 80,25 m ² (□85,50 m ²)
Required lawn grating:	92,00 m ²
Recommended surface material:	sand, wood chip, gravel, synth. impact protection

