DATA SHEET MULTIPLAY GRAVIS 2A

Text for invitation to tender | Item No: 51 5519 421



MATERIALS I SCOPE OF SUPPLY

Climbing equipment, final installation on location

Tower: stainless steel, V2A, with steel

plateau which surface is made of EPDM granules, and roof made of HDPE panel, 2 pc.

Post: stainless steel, V2A, 6 pieces

Climbing net: Herkules rope/plastic, 1 piece stainless steel, V2A, with 4 balls Climbing balls:

made of EPDM granules, 1 pc.

Layaway bow: stainless steel, V2A with 12

caps made of plastic, 1 pc.

Climbing wall: stainless steel, V2A, with 2 HDPE

panels, 1 piece

Herkules rope/plastic/wood, Wobble bridge:

lpc.

Parallel bars slide: stainless steel, V2A, 1 piece

stainless steel, V2A, 1 piece Slide:

plastic, 2 pieces Caps:

Decoration ball: EPDM granules, 4 pieces

steel, coated Foundation plates:

INSTALLATION

10 Foundations:

Installation according to our detailled mounting instructions, see www.stilum.com

TECHNICAL INFORMATION

Dimensions:

Main dimension: 4250 x 9500 mm

3320 mm Height: 880 ka Weight:

Capacity: acc. to normative

requirements

Dimension largest piece: 2550 x 700 x 3500

185 kg Heaviest piece:

Max. fall height: 2200 mm $71.34 \, \text{m}^2$ Impact area:

min. 80,25 m² Required safety slabs: $(\Box 85,50 \text{ m}^2)$

92.00 m²

Recommended

surface material:

Required lawn grating:

sand, wood chip, gravel,

synth, impact protection













