DATA SHEET MULTIPLAY GRAVIS 2B

Text for invitation to tender | Item No: 51 5519 422



MATERIALS I SCOPE OF SUPPLY

Climbing equipment, final installation on location

Tower: stainless steel, V2A, with

> steel plateau which surface is made of EPDM granules,

> and roof made of HDPE pa-

nel, 2 pieces

stainless steel, V2A, 6 pieces Post: Climbing net: Herkules rope/plastic, 1 pc. stainless steel, V2A, with 4 Climbing balls:

balls made of EPDM granu-

les, 1 piece

Climbing eye: stainless steel, V2A, 1 pc.

Wobble bridge: Herkules rope/plastic/wood,

1 pc

stainless steel, V2A, 1 piece Slide:

plastic, 2 pieces Caps:

Decoration ball: EPDM granules, 2 pieces

Foundation plates: steel, coated

TECHNICAL INFORMATION

Dimensions:

Main dimension: 6700 x 4150 mm

3320 mm Height: 675 ka Weight:

Capacity: acc. to normative

requirements

Dimension largest piece: Ø1410 x 1900 mm

170 kg Heaviest piece:

Max. fall height: 1500 mm 55,00 m² Impact area:

min. $62,00 \text{ m}^2 (\Box 75,00 \text{ m}^2)$ Required safety slabs: Required lawn grating: min. $68,00 \text{ m}^2 (\Box 75,00 \text{ m}^2)$

Recommended

sand, wood chip, gravel, surface material:

synth. impact protection

INSTALLATION

Foundations:



















Modified installation depth possible (special edition)

Installation according to our detailled mounting instructions, see www.stilum.com