DATA SHEET BOUNCING ELEMENT JUMP CIRCLE S

Text for invitation to tender | Item No: 514617xx1



MATERIALS I SCOPE OF SUPPLY

Bouncing element fully assembled for installation

basic frame: steel hot dip galvanized

Jumping surface: plastic slats cover: safety slabs

equipment: eyebolts M12, 4 pieces

SAFETY AND USER NOTES

- Kind of usage: standing/bouncing
- No somersaults, belly and back jumps
- No food / beverage
- No alcohol / drugs
- Wear shoes with flat sole
- No jewellery
- Spare parts have to be purchased from the manufacture only.

INSTALLATION

Combined frost protection and load bearing layer

Installation according to our detailled mounting instructions, see www.stilum.com

TECHNICAL INFORMATION

Dimensions:

Main dimension: Ø 1700 mm

Weight: 213 kg

capacity: acc. to normative

requirements, max. 200 kg

Dimensions largest piece: Ø 1700 x 375 mm

Heaviest piecel: 213 kg

Max. fall height: max. 1000 mm

Required free space: 1,50 m around the jumping

surface

3,50 m above the jumping

surface

Safety surfacing area: 11,58 m²
Required safety slabs: 16,00 m²
Required lawn grating: 20,00 m²

Surface material: grass, sand, wood chip,

gravel, synth. impact

protection







Colours:

23 = blue, 26 = black, 31 = signalyellow, 32 = signalgreen, 34 = signalred





