

DATA SHEET BOUNCING ELEMENT JUMP 6

Text for invitation to tender | Item No: 514606xx1



MATERIALS | SCOPE OF SUPPLY

Bouncing element fully assembled for installation

| | |
|------------------|---------------------------------------|
| basic frame: | steel hot dip galvanized |
| Jumping surface: | plastic slats |
| cover: | safety slabs |
| equipment: | eyebolts M12, 4 pieces for lifting |

SAFETY AND USER NOTES

- No somersaults, belly and back jumps
- No food / beverage
- No alcohol / drugs
- Wear shoes with flat sole
- No jewellery
- Spare parts for Bouncing element have to be purchased from the manufacture only.

INSTALLATION

Combined frost protection and load bearing layer

Installation according to our detailed mounting instructions, see www.stilum.com

TECHNICAL INFORMATION

Dimensions:

| | |
|---------------------------|--|
| Main dimension: | 2000x1750 mm |
| Jumping area: | Ø 1250 mm |
| Weight: | 330 kg |
| capacity: | acc. to normative requirements, max. 200 kg |
| Dimensions largest piece: | 2500 x 1750 x 375 mm |
| Heaviest piece: | 330 kg |

| | |
|----------------------|---|
| Max. fall height: | max. 1000 mm |
| Required free space: | 1,50 m around the jumping surface 3,50 m above the jumping surface |

| | |
|------------------------|--|
| Safety surfacing area: | 19,35 m ² |
| Required safety slabs: | 20,25 m ² |
| Required lawn grating: | 25,00 m ² |
| Surface material: | grass, sand, wood chip, gravel, synth. impact protection |

