

DATA SHEET BOUNCING ELEMENT JUMP XL

Text for invitation to tender | Item No: 514630xx1



MATERIALS | SCOPE OF SUPPLY

Bouncing element fully assembled for installation

basic frame:	steel hot dip galvanized
Jumping surface:	plastic slats
cover:	safety slabs
equipment:	eyebolts M12, 4 pieces for lifting

SAFETY AND USER NOTES

- No somersaults, belly and back jumps
- No food / beverage
- No alcohol / drugs
- Wear shoes with flat sole
- No jewellery
- Spare parts for Bouncing element have to be purchased from the manufacture only.

INSTALLATION

Combined frost protection and load bearing layer

Installation according to our detailed mounting instructions, see www.stilum.com

TECHNICAL INFORMATION

Dimensions:

Main dimension:	3000x2000 mm
Weight:	362 kg
capacity:	acc. to normative requirements, max. 200 kg
Dimensions largest piece:	3000 x 2000 x 375 mm
Heaviest piece:	362 kg

Max. fall height:	max. 1000 mm
Required free space:	2,00 m around the jumping surface 3,50 m above the jumping surface
Safety surfacing area:	29,75 m ²
Required safety slabs:	32,00 m ²
Required lawn grating:	36,00 m ²
Surface material:	grass, sand, wood chip, gravel, synth. impact protection

