

# DATA SHEET BOUNCING ELEMENT JUMP XS

Text for invitation to tender | Item No: 514615xx1



## MATERIALS | SCOPE OF SUPPLY

Bouncing element fully assembled for installation

basic frame:	steel hot dip galvanized
Jumping surface:	plastic slats
cover:	safety slabs
equipment:	eyebolts M12, 4 pieces for lifting

## SAFETY AND USER NOTES

- No somersaults, belly and back jumps
- No food / beverage
- No alcohol / drugs
- Wear shoes with flat sole
- No jewellery
- Spare parts for Bouncing element have to be purchased from the manufacture only.

## INSTALLATION

Combined frost protection and load bearing layer

Installation according to our detailed mounting instructions, see [www.stilum.com](http://www.stilum.com)

## TECHNICAL INFORMATION

Dimensions:

Main dimension:	1500x1500 mm
Weight:	208 kg
capacity:	acc. to normative requirements, max. 200 kg
Dimensions largest piece:	1500 x 1500 x 500 mm
Heaviest piece:	208 kg

Max. fall height:	max. 1000 mm
Required free space:	1,50 m around the jumping surface 3,50 m above the jumping surface
Safety surfacing area:	13,75 m <sup>2</sup>
Required safety slabs:	15,00 m <sup>2</sup>
Required lawn grating:	16,00 m <sup>2</sup>
Surface material:	grass, sand, wood chip, gravel, synth. impact protection

