


Mounting instructions bouncing element „jump XS“

Item no. 514615xx1



*Diagram 1: Overall view of the play equipment
Small bouncing element according to EN 1176:2017 Chapter 1 4.2.16.1.*

Mounting instructions bouncing element „jump XS“

Item no. 514615xx1




Diagram 2: Combined frost protection and load bearing layer

1. Select the play equipment location in consideration of the required safety area (see diagram 4: 4000 x 4000 mm).
2. Carry out excavation work for the foundation as shown in diagram 3.
pit size: (LxWxH) 1700 x 1700 x 550 mm
Excavation of the pit: 1,6 m³
Needed combined frost protection and load bearing layer material: 0,57 m³
Note: Due to the high weight, a lifting device is necessary
3. Create combined frost protection and load bearing layer as shown in diagram 2.
4. Screw the eyebolts into the existing holes and use as lifting point.
5. Lift Bouncing Element Jump XS and place it in the middle of the pit.
6. Unscrew eyebolts.
7. Fill the gap with parts of excavation.
8. Think about safety surface
9. For a maximum fall height of $\leq 1,00$ m safety surface must be according to EN 1176-1:2017 4.2.8.5 table 4.
For a bouncing element, the extent of the clearance must be 1,50 m horizontally around the jump surface, measured at each point of the edge, and 3,50 m above the jump surface.
10. Do not allow children to use the equipment before the installation has been finished.

Attention: If the play equipment has been incompletely installed or partly dismantled when carrying out maintenance and repair work, this may lead to particular risks of injury for the user. For this reason, make clearly visible that the equipment shall not be used in such cases.

Mounting instructions bouncing element „jump XS“

Item no. 514615xx1




Diagram 3: Cut through installed Bouncing Element Jump XS




Diagram 4: Top view