

DATA SHEET SPRINGRIDER MINA SWING

Text for invitation to tender | Item No: 51 3011 601



MATERIALS | SCOPE OF SUPPLY

Springrider, pre-mounted completely

Body:	structural composite lumber, larch, 1 piece
Handles:	stainless steel, V2A, 2 pieces
Tail:	stainless steel, V2A, 1 piece
Tube end caps:	ball made of EPDM caoutchouc, 1 piece
Spring:	spring steel Ø 20 mm Ø 200 x 400 mm height
Foundation anchor:	galvanized steel

TECHNICAL INFORMATION

Dimensions:

Main dimension:	900 x 690 mm
Height:	710 mm
Weight:	30 kg
Capacity:	acc. to normative requirements
Dimension largest piece:	900 x 690 x 1210 mm
Heaviest piece:	30 kg

Max. fall height:	560 mm
Impact area:	7,51 m ²
Required safety slabs:	10,50 m ²
Required lawn grating:	12,00 m ²
Recommended surface material:	grass, sand, wood chip, gravel, synth. impact protection

INSTALLATION

Foundations: 1
Modified installation depth possible
(special edition)

Installation according to our detailed mounting
instructions, see www.stilum.com

Please note the material information in the mounting- and maintenance instruction.

