

# DATA SHEET SEESAW SALI 4

Text for invitation to tender | Item No: 51 2515 402



## MATERIALS | SCOPE OF SUPPLY

Seesaw, pre-mounted completely

Seesaw bar:	stainless steel, V2A
Rack:	stainless steel, V2A with shaft made of stainless steel and so- ckets made of plastic
Handles:	stainless steel, V2A, with EPDM caout- chouc ball, 8 pieces
Seats:	EPDM caoutchouc with steel inlay, 4 pieces

## TECHNICAL INFORMATION

Dimensions:

Main dimension:	3530 x 460 mm
Height:	1095 mm
Weight:	106 kg
Capacity:	acc. to normative requirements
Dimensions largest piece:	3530 x 480 x 1545 mm
Heaviest piece:	97 kg

Max. fall height:	1450 mm
Impact area:	14,00 m <sup>2</sup>
Required safety slabs:	15,00 m <sup>2</sup>
Required lawn grating:	18,00 m <sup>2</sup>
Recommended surface material:	sand, wood chip, gravel, synth. impact protection

## INSTALLATION

Foundations: 1 plus 2 foundations  
for seesaw softeners

Modified installation depth possible  
(special edition)

Seesaw softeners must be concreted.

Installation according to our detailed moun-  
ting instructions, see [www.stilum.com](http://www.stilum.com)

