DATA SHEET MULTIPLAY TANTUM 2A

Text for invitation to tender | Item No: 51 7540 401



MATERIALS | SCOPE OF SUPPLY

Multiplay, final installation on location

Tower: stainless steel, V2A, with steel

plateau which surface is made of EPDM granules, plus walls

made of HDPE panels, 2 pieces

Roof: HDPE panels, 2 pieces
Tunnel slide: stainless steel, V2A, 1 piece

Wobble bridge: Herkules rope/rope/plastic,

1 piece

Climbing arc: stainless steel, V2A, 1 piece
Climbing net: Herkules rope/plastic, 1 piece

Balance rope: PP/plastic, 1 piece

Rope rail: Herkules rope/plastic, 2 piece Helix: stainless steel, V2A, 1 piece Disk climbing: stainless steel, V2A, with 11

pendulum seats made of EPDM caoutchouc and chains made

of stainless steel.

1 piece

Climbing wall: HDPE panels with climbing

holds, 3 pieces

Foundation plates: steel, coated

INSTALLATION

Foundations: 6

Installation according to our detailled moun-

ting instructions, see www.stilum.com

TECHNICAL INFORMATION

Dimensions:

Main dimension: 11500 x 4900 mm

Height: 5450 mm Weight: 2200 kg

Capacity: acc. to normative

requirements

Dimension largest piece: 1730 x1250 x 5900 mm

Heaviest piece: 620 kg

Max. fall height: 3000 mm Impact area: 82,50 m²

Required safety slabs: min. 91,00 m² $(\Box 112,50 \text{ m}^2)$

Required lawn grating: min. $104,00 \text{ m}^2$ ($\square 120,00 \text{ m}^2$)

Recommended

surface material: sand, wood chip, gravel,

synth. impact protection













